

NEMA Standards Publication LL 10-2020

Replacing HID Lamps with LED Lamps: Light Output Equivalency Claims

Published by

National Electrical Manufacturers Association 1300 North 17th Street, Suite 900 Rosslyn, VA 22209

© 2021 National Electrical Manufacturers Association. All rights reserved including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, and without the prior written permission of the publisher.

Printed in the United States of America.

www.nema.org

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) Standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus Standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its Standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this Standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other Standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety–related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

1	Ove	erview	1
2	Gen	neral	2
2	2.1	Scope	2
2	2.2	References	2
3	Basi	sics of HID lamps	3
4	Adju	ustments to Luminous Flux	6
4	l.1	Lumen Maintenance Differences.	6
4	.2	Spectral Effects	6
	4.2.1	1 Mesopic Lighting	6
	4.2.2	2 Color Rendering Effects	7
	4.2.3	3 Spectrum Correction	7
4	.3	Other Effects	8
5	Calc	culation of Equivalency	8
6	Con	nclusions1	0
7	App	pendix: Directionality Corrections	1

Figures

Figure 1: Initial light output as a function of input wattage, for HPS lamps	5
Figure 2: Initial light output as a function of input wattage, for metal halide lamps.	5
Figure 3: An example of a directional highbay LED replacement lamp [20]. The LEDs	
are mounted on the downward facing surface.	.11
Figure 4: Example of a Corn-cob lamp [21], with LEDs (not visible) mounted on the horizontal surface opposite from the base. The photometric plot (the lamp base is at 180°) shows the light at 0°	
(and nearby angles) from the LEDs mounted on the horizontal surface.	. 12
Figure 5: Example of a corn-cob lamp without LEDs mounted on the top (or bottom)	
horizontal surfaces [22]. The photometric plot is symmetric with no light at 0° and 180°.	
The emission of light in any direction perpendicular to the lamp axis is Lambertian	. 13
Figure 6: Example of an LED HID replacement lamp [23], intended for use in Wall Pack fixtures. Unlike the examples in Figure 4 and Figure 5, LEDs are located only on part of the cylindrical body	
of the heatsink, producing a directional beam.	. 14
Figure 7: Example of a 250W metal halide HID lamp, with its light distribution	. 15
Figure 8: Light distribution of the lamp in Figure 7, averaged over the C planes (blue curve). The green-shaded area is the uplight from the lamp, that would not be generated by an	
LED source with a lambertian emission pattern (orange curve).	. 16

< This page intentionally left blank. >

1 Overview

Light-emitting diode (LED) lamp products designed to replace high-intensity discharge (HID) lamps are becoming common in the marketplace. However, there are large variations in the luminous flux of LED lamps that claim to be equivalent to a particular HID lamp. These variations are leading to confusion for customers and an uneven playing field for manufacturers. For other lamp types, the variation in claimed equivalency is not presently a concern. The Energy Star lamps specification carefully defines equivalency to incandescent or halogen lamps. With LED replacement lamps for linear fluorescent lamps, there is also limited variation in the light output of the linear fluorescent lamps that are being replaced. HID equivalency is more difficult to define. Because of the large variation in lamp wattages, light output, and directionality provided by the luminaire, the concept of equivalency is more complicated for HID lamp replacement.

We expect manufacturers to use this Standard during the preparation of their HID equivalency claims and to reference it as support for those claims. End users, specifiers, and entities establishing requirements may also use it to ensure that sufficient light output is obtained in their applications.

2 General

2.1 Scope

The purpose of this Standard is to describe a method to establish reasonable claims of initial light output equivalency for single-ended omnidirectional LED replacement lamps that are intended to replace HID lamps.

The method accounts for two factors that influence the equivalency claims:

- a. Improved lumen maintenance vs. HID. Because LED lamps have a longer useful life and their light output degrades more slowly than most HID lamps, this factor results in initial luminous flux for an LED replacement lamp that is lower than the equivalent HID lamp. This factor is independent of the luminaire.
- b. The spectrum of the light, in the case of outdoor (or other low-light-level) applications. In darker environments, reaction time is faster, recognition of objects and people is more accurate, and the perception of brightness is higher if the light source has high color rendering. This factor depends on the spectrum of the light and is independent of the luminaire.

The Standard does not address other lamp characteristics, such as safety, physical dimensions, other light quality parameters, or reporting requirements. Because of the strong dependence on applications, it also does not provide corrections for the directionality of a light source, though an informative appendix addressing directionality is included.